

 **BENNE – POLIPI**

 **CLAMSHELL BUCKETS – POLYP GRABS**

 **BENNES PRENEUSES – GRAPPINS À POLYPES**

 **ZWEISCHALENGREIFER – MEHRSCHALENGREIFER**

 **CUCHARAS – PULPOS**

 **ГРЕЙФЕРЫ - МНОГОЧЕЛЮСТНЫЕ ГРЕЙФЕРЫ**

 **KARAKLI KOVA TUTUCULAR**




 **قواديس محوريه**

06





BENNE BIVALVE CON CILINDRO ORIZZONTALE CLAMSHELL BUCKET WITH HORIZONTAL CYLINDER

Modelli Models	Capacità Capacity	Peso Weight	Denti Teeth	A	B	C	D	L	Portata Load capacity	Forza utile Closing force	Pressione Pressure	 	Rotatore consigliato Suggested rotator	
	lt	kg	n°	mm	mm	mm	mm	mm	kg	daN	bar	ton*	ton**	type
FCB 35	35	32	3	456	624	357	304	305	100	433	200	0,1-0,3	0,8-1,0	FR 15 - FR 35
FCB 50	50	52	4	626	895	492	390	330	150	821	200	0,2-0,4	0,8-1,2	FR 35
FCB 100	100	85	4	770	1100	605	480	350	200	974	200	0,2-0,5	1,0-1,5	FR 35 - FR 35F
FCB 125	125	134	4	840	1200	660	523	450	250	1737	200	0,3-0,7	1,2-1,7	FR 35 - FR 35F
FCB 155	155	143	4	840	1200	660	523	550	350	1737	200	0,4-0,8	1,2-2,0	FR 35 - FR 35F
FCB 175	175	152	4	840	1200	660	523	650	350	1737	200	0,5-0,9	1,5-2,2	FR 35 - FR 35F
FCB 205	205	161	6	840	1200	660	523	750	450	1737	200	0,6-1,0	1,8-2,5	FR 35 - FR 35F
FCB 225	225	170	6	840	1200	660	523	850	450	1737	200	0,7-1,2	1,8-3,0	FR 35 - FR 35F
FCB 325	325	208	6	1040	1430	780	565	800	700	1477	200	0,9-1,3	2,5-3,5	FR 50 - FR 55F
FCB 360	360	220	8	1040	1430	780	565	900	700	1477	200	0,9-1,5	2,5-4,0	FR 50 - FR 55F
FCB 425	425	232	8	1040	1430	780	565	1000	700	1477	200	1,0-1,6	3,0-5,0	FR 50 - FR 55F
FCB 525	525	315	8	1200	1640	905	660	1000	1000	1550	200	1,0-2,0	4,0-7,0	FR 50 - FR 55F
FCB 625	625	343	8	1200	1640	905	660	1200	1000	1550	200	1,0-2,0	4,0-7,0	FR 85 SXF
FCB 150 SX	150	260	3	1206	1830	900	620	360	1000	1520	200	0,6 - 1,5	4,0 7,0	FR 85 SXF
FCB 250 SX	250	269	4	1206	1830	900	620	430	1000	1520	200	0,6 - 1,8	4,0 7,0	FR 85 SXF
FCB 300 SX	300	287	4	1206	1830	900	620	630	1300	1520	200	0,8-2,0	4,0-7,0	FR 85 SXF
FCB 400 SX	400	296	6	1206	1830	900	620	730	1300	1520	200	0,8-2,0	4,0-7,0	FR 85 SXF
FCB 500 SX	500	305	6	1206	1830	900	620	830	1300	1520	200	0,8-2,2	4,0-7,0	FR 85 SXF
FCB 600 SX	600	323	8	1206	1830	900	620	1030	1300	1520	200	0,8-2,4	4,0-8,0	FR 85 SXF

In conformità EN 2006 42 CE - According to EN 2006 42 EC

* portata gru a braccio sfilato - crane capacity at max reach

** peso escavatore - excavator weight

▶ **Valvola di blocco optional - Optional block valve**
 Standard solo sui modelli SX - Standard only in SX models



▶ **Possibilità di montare denti**
 Possibility to mount teeth

